





# PowerFlow HP Pump NFPA 1906 Selection Guide

The following PowerFlow HP Series portable pumps are capable of meeting the Wildland Fire Apparatus rated capacities shown in accordance with the 2016 edition of NFPA 1906.

50 GPM @ 100 PSI	50 GPM @ 150 PSI	50 GPM @ 250 PSI	150 GPM @ 100 PSI
HP75-YD9	HP200-B18	HP75-B18	HP200-B23
HP300-B18	HP200-B23	HP75-B23	HP200-H20
HP400-B18	HP200-KBD24	HP75-KBD24	HP200-KBD24
HP400-B23	HP275-B35	HP100-B23	HP275-B35
		HP100-KBD24	HP300-B23
			HP300-KBD24
			HP350-KBD39
			HP450-B35

Refer to individual performance curves below for maximum pump performance and lift capabilities.

HP75-YD9	<b>FSG-CRV-01461</b>	HP200-KBD24	<b>FSG-CRV-01401</b>
HP75-B11	<b>FSG-CRV-01449</b>	HP275-B35	<b>FSG-CRV-01459</b>
HP75-B18	<b>FSG-CRV-01451</b>	HP300-B18	<b>FSG-CRV-01453</b>
HP75-B23	<b>FSG-CRV-01473</b>	HP300-B23	<b>FSG-CRV-01457</b>
HP75-KBD24	<b>FSG-CRV-01474</b>	HP300-KBD24	<b>FSG-CRV-01402</b>
HP100-B23	<b>FSG-CRV-01455</b>	HP350-KBD39	<b>FSG-CRV-01463</b>
HP100-KBD24	<b>FSG-CRV-01400</b>	HP400-B18	<b>FSG-CRV-01454</b>
HP200-B11	<b>FSG-CRV-01450</b>	HP400-B23	<b>FSG-CRV-01458</b>
HP200-B18	<b>FSG-CRV-01452</b>	HP400-KBD24	<b>FSG-CRV-01403</b>
HP200-B23	<b>FSG-CRV-01456</b>	HP400-KB39	<b>FSG-CRV-01464</b>
HP200-H20	<b>FSG-CRV-01489</b>	HP450-B35	<b>FSG-CRV-01460</b>

ECN	REV	CHANGED FROM	BY	DATE	APVD	   					
CFL3628	A	RELEASE FOR DOCUMENTATION	JRP	21JAN2016	GC	<small>COPYRIGHT © Not to be reproduced or used to make other drawings or machinery.</small>	<b>DRAWN</b>	JRP	SIZE	<b>DRAWING NUMBER</b>	REV
CFL4150	B	ADDED HP75-B23, HP75-KBD24 & HP200-H20	JRP	24JUL2017	JRP		<b>APPROVED</b>	GC	<b>A</b>	<b>FSG-CRV-01448</b>	<b>B</b>
						<b>DATE</b>	21JAN2016	SCALE 1:1			<small>SHEET 1 OF 1</small>