

PowerFlow HPX75-B18

You deserve fire pumps that you can depend on, first time, every time. That's why the Hale high pressure pump range are designed to be tough and dependable performers. Hale has over 100 years' experience making fire pumps so you can be sure your Hale pump will deliver performance when you need it.

Features

- Flows ranging from 15 GPM @ 325 PSI to 135 GPM @ 50 PSI
- Ultra-reliable Briggs & Stratton 18-HP 4-cycle V-Twin gasoline engine
- Electric start with recoil backup
- Anodized aluminum alloy pump head and body
- Pump head and body coupled together with stainless steel band clamp for easy serviceability
- Bronze impeller and renewable wear ring
- Self-adjusting mechanical seal
- Exhaust gas venturi priming
- 2.0" NPT suction connection; 1.5" NPT discharge

Applications/Solutions

- Fire OEMs
- Firefighting - Wildland Forestry



Specifications

Certification(s)	  
Warranty	
Weight	71 kg
Length	21 inches (533 mm)
Width	18 inches (457 mm)
Height	20 inches (508 mm)
Application Solutions Portables	Slip-on
Performance	High Pressure, Low Flow
Application Type	High Pressure, Low Flow
Dimensions	Extra Small
Priming Option	Manual, Exhaust, Electric

