

## Powerflow 8/5 Single Discharge

The GP 8/5 is a compact and lightweight portable fire pump with a rated performance of 800l/min at 5 bar of pressure with a 3 metre lift.. Powered by 18HP Briggs and Stratton engine, this pump uses a single discharge valve and is available with exhaust priming system, electric or manual starting.

### Features

- Ultra compact and lightweight – frees up locker space for other equipment
- Up to 12% smaller and 10% lighter than comparable pumps
- A range of flows to suit differing needs
- Priming - exhaust gas ejection or hand priming versions (single discharge only)



### Specifications

Certification(s)	
Weight	154 lbs (dry)
Length	22 inches (555 mm)
Width	19.3 inches (490 mm)
Height	23 inches (584 mm)
Flow (GPM)	308 gpm @ 43.5 psi
Flow (LPM)	1400 l/min @ 3bar
Rated Output LPM	800 l/min @ 3 bar
Rated Output GPM	176.2 gpm @ 43.5 psi
Maximum flow - High pressure	1420 l/min
Maximum outlet pressure bar	8.2 bar
Maximum outlet pressure psi	119 psi
NFPA 1906 or EN Rated Capacity	800 l/min @ 5 bar
Application Solutions Portables	Transportable / Self Contained
Performance Application Type	Low Pressure, Medium Flow
Dimensions	Extra Small
Priming Option	Manual, Exhaust,

