

## FoamLogix 2.1A


Hale's FoamLogix 2.1A foam system is a flow based foam concentrate proportioning system that uses a field-proven flow sensor assembly to measure actual water flow from the fire pump discharge. The digital input of the flow sensor and the actual output of the positive displacement piston foam concentrate pump are constantly compared and updated by the controller which automatically adjusts the desired foam concentrate rate injected into the discharge. It has full function digital control with push button operation for ease of use. The digital foam system removes the traditional pressure restrictions of other foam systems so it is unaffected by hose length, flow rate, or pressures.



### Features

- 8 l/min (2.1 gpm) Piston Pump Computer controlled Class A foam proportioning at a value price
- Push button proportioning
- Arrow buttons allow changing foam percentage from 0.1% to 10.0%
- Digital control means the operator presses one button for precise foam delivery every time
- Available fully integrated onto a new Hale pump or in kits to fit other pump brands
- Wide range of flow sensor options from pipe saddle clamps to stainless steel weld-on fittings are available

### Specifications

Certification(s)	
Brand	SmartFoam
Length	16.4 inches (416 mm)
Width	13.1 inches (333 mm)
Height	6.9 inches (175 mm)
Amperage	40 amps @ 12V, 20 amps @ 24V
Rated Output LPM	7.9 LPM
Rated Output GPM	1.74 GPM

